


POS-NR.	DESCRIPTION	QTY
1	UHV connector 15 pin (female)	2
2	ribbon cable 15 pin PTFE insulated	1

Connecting view connector			Connecting view cable		
Con1	Con2	Cable	Cable	Con1	Con2
1	8	1	1	1	8
2	7	3	2	9	15
3	6	5	3	2	7
4	5	7	4	10	14
5	4	9	5	3	6
6	3	11	6	11	13
7	2	13	7	4	5
8	1	15	8	12	12
9	15	2	9	5	4
10	14	4	10	13	11
11	13	6	11	6	3
12	12	8	12	14	10
13	11	10	13	7	2
14	10	12	14	15	9
15	9	14	15	8	1



Bemerkungen (Remarks)				Freimaßtoleranz (Standard Toleranz)		Maßstab (Scale)	Rauheit (Roughness)		europ.Projektion	
All informations provided in this drawing is considered to be confidential, proprietary and secret information. It is intended only for the use of individual or entity to whom it is sent. Individual or entity agrees to not disseminate or copy this information to anyone other than originally specified without the written consent Allestra GmbH.				Datum		1:10	Material, Standard Oberfläche (Treatment)		Kanten (edges)	
				Design	14.07.2016	JB	Bezeichnung (Title)		Gewicht (weight)	
				Drawn	19.10.2016	FW				
				Check						
							Zeichnungsnummer (Drawing No.)		Revision	
							Datei (File)		Format	
Index	Modification	Datum	Name							

allestra

cable with 2 of 15 pin female connectors PEEK
1x 15 way ribbon cable

380-D15-FFPPT-X

Page: 2
Pages: 5

Format A4