

connecting view connector				connecting view cable			
cable	Con1	Con2	Cable	cable	Cable	Con1	Con2
	1	8	1		1	1	8
	2	7	3		2	9	15
	3	6	5		3	2	7
	4	5	7		4	10	14
	5	4	9		5	3	6
	6	3	11		6	11	13
	7	2	13		7	4	5
	8	1	15		8	12	12
	9	15	2		9	5	4
	10	14	4		10	13	11
	11	13	6		11	6	3
	12	12	8		12	14	10
	13	11	10		13	7	2
	14	10	12		14	15	9
	15	9	14		15	8	1

POS-NR.	DESCRIPTION	QTY
1	UHV connector 15 pin (female)	2
2	ribbon cable 15 pin Kapton insulated	1

1

8

15

9

15

1

connector 1 / 211-FS15-PK basic for feedthrough

2

Lx +0/-20

1

9

15

1

8

connector 2 / 211-FS15-PK basis customer

Bemerkungen (Remarks)				Freimaßtoleranz (Standard Toleranz)		Maßstab (Scale)		Rauheit (Roughness)		europ.Projektion	
All informations provided in this drawing is considered to be confidential, proprietary and secret information. It is intended only for the use of individual or entity to whom it is sent. Individual or entity agrees to not disseminate or copy this information to anyone other than originally specified without the written consent Allectra GmbH.						1:10					
				Datum		Name		Material, Standard Oberfläche (Treatment)		Kanten (edges)	
				Design		JB		Bezeichnung (Title)		Gewicht (weight)	
				Drawn		FW		cable with 2 of 15 pin female connectors PEEK		g	
				Check				1x 15 way ribbon cable		56.19	
										Page: 2	
										Pages: 5	
								Zeichnungsnummer (Drawing No.)		Revision	
								380-D15-FFPR-X			
Index				Modification		Datum		Datei (File)		Format	
								C:\PDMStore\I\C:\PDMStore\		A4	